


INDUCTION HEATING METHOD FOR LAMINATED IRON CORE AND APPARATUS THEREFOR

Patent number: JP60074417
Publication date: 1985-04-26
Inventor: OKAMOTO TATSUMI
Applicant: OKAMOTO TATSUMI;; MITSUI MFG
Classification:
- international: H01F41/02
- european: H01F41/02A3; H02K15/02; H05B6/02B
Application number: JP19830181232 19830929
Priority number(s): JP19830181232 19830929

Report a data error here

Abstract of JP60074417

PURPOSE:To efficiently heat the entire part of laminated iron core by continuously carrying a laminated iron core between a pair of inductors for heating. **CONSTITUTION:**A pair of inductors for heating 20a, 20b are provided opposingly and the shape of section of it is rectangular with the longer sides being set longer a little than the diameter of laminated iron core 21 and the shorter sides being set sufficiently shorter than the longer sides. The magnetic pole is generated by applying an alternative current to the coils of inductors 20a and 20b. The iron core 21 is arranged so that direction of magnetic flux ϕ generated between the inductors 20a, 20b matches the thickness direction of iron core and it is continuously carried out in the direction of arrow mark A.



Data supplied from the esp@cenet database - Worldwide

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **60074417 A**

(43) Date of publication of application: **26.04.1985**

(51) Int. Cl. **H01F 41/02**

(21) Application number: **58181232**

(22) Date of filing: **29.09.1983**

(71) Applicant: **OKAMOTO TATSUMI**

MITSUI HAITETSUKU:KK

(72) Inventor: **OKAMOTO TATSUMI**

(54) INDUCTION HEATING METHOD FOR LAMINATED IRON CORE AND APPARATUS THEREFOR

iron core and it is continuously carried out in the direction of arrow mark A.

COPYRIGHT: (C)1985,JPO&Japio

(57) Abstract:

PURPOSE: To efficiently heat the entire part of laminated iron core by continuously carrying a laminated iron core between a pair of inductors for heating.

CONSTITUTION: A pair of inductors for heating 20a, 20b are provided opposingly and the shape of section of it is rectangular with the longer sides being set longer a little than the diameter of laminated iron core 21 and the shorter sides being set sufficiently shorter than the longer sides. The magnetic pole is generated by applying an alternative current to the coils of inductors 20a and 20b. The iron core 21 is arranged so that direction of magnetic flux ϕ generated between the inductors 20a, 20b matches the thickness direction of

